

LogMan II

Transferring Container Data to any PC for further analysis

- Used for manual or automatic download/retrieval of reefer containers datalogger information
- For download/retrieval and transferring of logs to computers for subsequent analysis and/or storage using the LogView software
- Set-up of container data such as container ID, date and time, etc.
- Calibration of cargo probes
- Update of software in reefer containers.
- Setup of genset configuration

Description

The LogMan II is based on an updated platform, the Workabout Pro S Second Generation Hand-Held Computer.

This updated platform offers several benefits for the daily user due to the improved user interface and additional support for the Thermo King SG+ genset controller.

LogMan II plays an important function in day-to-day container handling. Besides the specific download functionality, LogMan II is supplied with a number of additional facilities that assist in the routine handling of refrigerated containers, such as container set-up and probe calibration facilities.

The downloaded/retrieved container data can be transferred to any specified PC for further analysis, using LogView.

Applications

- PTI shops
- Repair shops
- Vessels
- Terminals



Environmental Specifications:

Operating temperature	-10°C < T _{op} < 50°C
Ingress Protection	IP 65
Shock	26 drops of 5 ft. (1.5 meters) to polished concrete
Humidity	5-95% RH non-condensing

Physical dimensions:

Length	190 mm
Width	98 mm
Height	44 mm
Weight (with battery)	491 g

Electrical specification:

Power supply	Auto-ranging: AC 100 - 240 V, 50/60 Hz
Rechargeable battery (included)	3,7 V, 3000 mAh

Accessories:

Controller retriever cable for old type Daikin units	P/N 5062-005
USB tether cable	P/N 1189-155
Protective Carrying Case	P/N 1189-154
Spare 3Ah Battery	P/N 1189-156

LogMann II (P/N 1189-004) - Included items:

Hand Held device (PSION Workabout Pro S 3G) with 256 MB storage capacity
LogMan II software installed
Hand strap
Rechargeable battery
Getting started user instruction
Docking Station
USB Cable (1,5 meter)
Controller retriever cable

Supported controllers:

Thermo King	MP-4000 MP-3000a MP-3000 MPC2000ID MPC2000 μP-A+ and μP-D
Thermo King	SG+ genset
Carrier	Microlink 3 Microlink 2i Mikrolink 2
Daikin	DECOS IIIg DECOS IIIf DECOS IIIe DECOS IIIId DECOS IIIc DECOS IIIb DECOS V
Mitsubishi	MMCC IIIA
MCI/Starcool	RCCU5 SCC6